



SUZUKI Jimny



Imágenes utilizadas de manera ilustrativa.



Jimny GL

- Motor gasolina 1.5, 4 cilindros, 16 válvulas, 100 HP
- Transmisión Automática de 4 velocidades
- Sistema ALLGRIP PRO (4WD)
- Suspensión delantera McPherson y trasera con barra de torsión con resortes helicoidales
- Control de Tracción
- Control de estabilidad (ESP)
- Asistente de ascenso y descenso en pendientes
- Distribución electrónica de frenado
- Frenos de disco delanteros con sistema ABS y EBD
- Bolsas de aires frontales chofer y pasajero
- Cristales, seguros y retrovisores acción eléctrica
- Aire acondicionado Manual
- Asientos tapizados en tela
- Radio AM/FM/MP3/Bluetooth
- Entrada USB Externa
- Control de radio en el volante
- Volante con ajuste vertical
- Barras laterales contra impacto

- Aros de aleación de 15"
- Luces de halógeno frontales y traseras
- Dirección electrónicamente asistida
- Alarma integrada
- Sistema ISOFIX
- Faros antiniebla

Jimny GLX

También incluye:

- Aire acondicionado Digital
- Radio Touch de 7" Bluetooth con Apple CarPlay y Android Auto
- Cruise Control
- Volante forrado en piel
- Luces LED frontales con limpiadores de faros
- Luggage Box (cajón trasero para guardar objetos)



androidauto

Major Specification

Number of doors		3	
Engine		Petrol	
		1.5L VVT	
Drive system		Part-time 4WD (ALLGRIP PRO)	
Transmission		SMT	4AT
DIMENSIONS			
Overall length	Front bumper to rear bumper	mm	3,480
	Front bumper to spare wheel	mm	3,625
Overall width		mm	1,645
Overall height		mm	1,725
Wheelbase		mm	2,250
Tread	Front	mm	1,395
	Rear	mm	1,405
Minimum turning radius		m	4.9
Minimum ground clearance		mm	210
Approach angle		deg.	37
Ramp breakover angle		deg.	28
Departure angle		deg.	49
CAPACITIES			
Seating capacity	persons		4
Luggage capacity	Max. volume	litres	830
	Rear seatback folded (VDA method)	litres	377 *
	Rear seatback raised (VDA method)	litres	85 *
Fuel tank capacity	litres		40
ENGINE			
Type			K15B
Number of cylinders			4
Number of valves			16
Piston displacement	cm ³		1,462
Bore x stroke	mm		74.0 x 85.0
Compression ratio			10
Maximum output	kW/rpm		75/6,000
Maximum torque	N·m/rpm		130/4,000
Fuel distribution			Multipoint injection
TRANSMISSION			
Type		SMT	4AT
Gear ratio	1st	4.425	2.875
	2nd	2.304	1.568
	3rd	1.674	1.000
	4th	1.190	0.697
	5th	1.000	-
	Reverse	5.151	2.300
Final gear ratio		4.090	4.300
Transfer gear ratio	High	1.000	1.320
	Low	2.002	2.644
CHASSIS			
Steering			Recirculating ball
Brakes	Front		Solid disc
	Rear		Drum, leading and trailing
Suspension	Front		3-link rigid axle with coil spring
	Rear		3-link rigid axle with coil spring
Tyres			195/80R15
WEIGHTS			
Kerb weight (min./with full options)	kg	1,090/1,135	1,110/1,135
Gross vehicle weight	kg		1,435
PERFORMANCE			
Maximum speed	km/h	145	140

All figures are manufacture's data and may vary for each market
 * Measured without luggage box.

